
Flask-Pure Documentation

Release 0.6.dev0

Philip Xu

Dec 17, 2020

Contents

1 Quick Start	3
2 How It Works	5
3 License	7
4 Links	9
5 Caveat	11
6 Configuration	13
6.1 PURECSS_CDN values	13
7 Template	15
8 Pure.css Version	17
9 API	19
10 Contributors	21
11 Changelog	23
11.1 Version 0.5	23
11.2 Version 0.4	23
11.3 Version 0.3	23
11.4 Version 0.2	23
11.5 Version 0.1	23
Python Module Index	25
Index	27

Flask-Pure is an extension to [Flask](#) that helps integrate [Pure.css](#) to your Flask application.

CHAPTER 1

Quick Start

0. Installation

```
pip install Flask-Pure
```

1. Configuration

```
from flask import Flask, render_template
from flask_pure import Pure

app = Flask(__name__)
app.config['PURECSS_RESPONSIVE_GRIDS'] = True
app.config['PURECSS_USE_CDN'] = True
app.config['PURECSS_USE_MINIFIED'] = True
Pure(app)

@app.route('/')
def hello():
    return render_template('hello.html')

if __name__ == '__main__':
    app.run(debug=True)
```

2. In templates/hello.html:

```
{% extends "pure/layout.html" %}
{% block title %}Hello world from flask-pure{% endblock %}

{% block nav %}
<div class="pure-menu pure-menu-horizontal">
    <!-- ... -->
</div>
{% endblock %}

{% block content %}
```

(continues on next page)

(continued from previous page)

```
<h1>Hello world</h1>
{% endblock %}
```

3. Profit!

CHAPTER 2

How It Works

Once registered, this extension provides a template variable called `pure`, it has a property named `css` that will be rendered as HTML `<link>` tag to the `Pure.css` stylesheets either from free CDN or be served from a bundled blueprint, also called `pure`.

A `{{ pure.css }}` inside `<head>` tag is all you need.

A bare bone HTML5 template is also available as `pure/layout.html`. Please check out the example in code repository and documentation for details.

CHAPTER 3

License

BSD New, see LICENSE for details.

CHAPTER 4

Links

- [Documentation](#)
- [Issue Tracker](#)
- [Source Package @ PyPI](#)
- [Mercurial Repository @ bitbucket](#)
- [Git Repository @ Github](#)
- [Git Repository @ Gitlab](#)
- [Development Version](#)

CHAPTER 5

Caveat

The stylesheet provided by template variable `pure.css` is the ‘Rollups’ version with all the modules in Pure. The responsive grids module that included by default can be turned off explicitly.

Thus, this extension is an ‘all-or-nothing’ approach, there is no plan to support selectable modules currently, as it is so trivial to roll your own.

The conditional IE 8/9 hack are not included, please refer to Pure’s official documentation if this is the concern.

CHAPTER 6

Configuration

Option	Description
PURECSS_RESPONSIVE_GRID	If <code>True</code> , the responsive grids module will be included as well. Default value is <code>True</code>
PURECSS_USE_CDN	If <code>True</code> , css files will be served from CDN. If <code>False</code> , local copies of css files will be served. Default value is <code>True</code>
PURECSS_CDN	If <i>PURECSS_USE_CDN</i> is <code>True</code> , css files will be served from this CDN. Default value is <code>unpkg</code> , as recommended by Pure.css, for list of CDNs, see next section
PURECSS_USE_MINIFIED	If <code>True</code> , the minified version of css files will be used. Default value is <code>True</code>

6.1 PURECSS_CDN values

Available CDNs as listed on <http://purecss.io/>

CDN	PURECSS_CDN Value
unpkg	unpkg
cdnjs	cdnjs
jsDelivr	jsdelivr
KeyCDN	keycdn
OSS MaxCDN	maxcdn
RawGit	rawgit
Staticfile	staticfile

CHAPTER 7

Template

In addition to providing Pure.css static assets, Flask-Pure comes with HTML5 template located in `pure/layout.html` for layout.

Predefined Blocks	Purpose
<code>html_attribs</code>	<code><html></code> 's attributes
<code>head</code>	all content inside <code><head></code> and <code></head></code>
<code>meta</code>	for all <code><meta></code> tags
<code>title</code>	content inside <code><title></code> and <code></title></code>
<code>style</code>	links to css stylesheets
<code>body_attribs</code>	<code><body></code> 's attributes
<code>body</code>	all content inside <code><body></code> and <code></body></code>
<code>nav</code>	navigation links
<code>content</code>	main content
<code>script</code>	embedded javascript

CHAPTER 8

Pure.css Version

The bundled version of Pure.css is v0.6.2

Flask-Pure - a Flask extension for Pure.css

class flask_pure.**Pure** (*app=None*)

Flask-Pure extension

provides base template layout as `pure/layout.html` and links to the Pure.css static assets.

css

property the will be rendered as Pure.css `<link>` tags

init_app (*app*)

create and register a blueprint with the Flask application.

Parameters **app** – Flask application instance

CHAPTER 10

Contributors

A huge thanks to all of our contributors:

- Bastian Kuhn <<https://github.com/Bastian-Kuhn>>
- Philip Xu <<https://github.com/pyx>>

11.1 Version 0.5

- Updated Pure.css version to 0.6.2

11.2 Version 0.4

- Updated Pure.css version to 0.6.1
- Added alternate CDNs support

11.3 Version 0.3

- Switched CDN url to https version (Contributed by Bastian Kuhn)

11.4 Version 0.2

- Added option to turned off the responsive grids module
- Used an instance of extension as namespace instead of a single template variable

11.5 Version 0.1

- Initial public release

f

`flask_pure`, [19](#)

C

`css` (*flask_pure.Pure attribute*), [19](#)

F

`flask_pure` (*module*), [19](#)

I

`init_app()` (*flask_pure.Pure method*), [19](#)

P

`Pure` (*class in flask_pure*), [19](#)